

Farola LED Pemali 100W



Referencia	201605022	201605023	201605024
Tipo de LED	SMD	SMD	SMD
Potencia (W)	100W	100W	100W
Testeo flujo luminoso (nominales)	Esfera 360°	Esfera 360°	Esfera 360°
Testeo flujo luminoso (útiles)	Esfera 360	Esfera 360	Esfera 360
Lúmenes nominales	13.000Lm	13.000Lm	13.000Lm
Lúmenes útiles	12.000Lm	12.000Lm	12.000Lm
Temperatura (K)	4.000K	5.700K	6.500K
Ángulo	140x70	140x70	140x70
PF	0,9	0,9	0,9
CRI	80	80	80
On/Off	15.000	15.000	15.000
Horas de vida	30.000h.	30.000h.	30.000h.
Amperios (mA)	434mA	434mA	434mA
IP	IP65	IP65	IP65
IK	IK7	IK7	IK7
Aislamiento (KV)	5	5	5
Driver reemplazable	No	No	No
Flicker free	Sí	Sí	Sí
Luminaria LED reemplazable	No	No	No
Longitud cable (cm)	30cm	30cm	30cm
Material principal	Aluminio	Aluminio	Aluminio
Material secundario	PC	PC	PC
Color principal	Gris	Gris	Gris
Diámetro (mm) (Ø)	60mm	60mm	60mm
Voltaje (V) (Mínimo)	160V	160V	160V
Voltaje (V) (Máximo)	265V	265V	265V
Hz	50/60Hz	50/60Hz	50/60Hz
Tipo embalaje	Caja	Caja	Caja

